



BL-02 BAS CONTROLLER TRAINING UNIT

The BL-02 is designed specifically for training DDC/BAS technicians and programmers who work with programmable unitary controllers. Graphical object oriented programming is presented using the non-proprietary, open-licensed Sedona Framework®.

Specifications

Power Requirements: 20W 24VDC (via 120VAC to 24VDC Wall Adapter)

Operating Temperature: 55°F to 85°F

Storage Temperature: 10°F to 110°F

Relative Humidity: 10 to 95% RH non-condensing

Mounting: Benchtop

Shipping Weight: 20 lbs

Dimensions: 17"W x 12"H x 7"D

Features

- Programmable Sedona 22 point unitary controller with BACnet IP, and web interface
- Instrument panel with Input/Output components and 24VDC posts
- 0-10 VDC Digital meter, 2-10v Belimo actuator
- 24VDC 1.5A Wall adapter
- Senva AQW Wall Setter with integral temperature, setpoint slider and CO2 sensor
- USB Drive with Course Curriculum and Setup/support documents

The BL-02 DDC/BAS Programming system can be purchased in these versions:

BL-02-Bc22 – Contemporary Controls BAScontrol22 controller, Senva wall setter, BAS Toolkit software, Intro to Sedona Course Curriculum (USB Drive). Full 1 yr. warranty.

BL-02-DIN – DIN rail mount (No controller included). Limited 1yr. warranty. No curriculum included. Note: DIN rail model requires some final user wiring due to lack of controller.



Shipping Weight: 7 lbs.

Shipping Dimensions: 20" L x 14" W x 14" H

